

JOLT. Turbo

- 35 watt halogen task light
- Superior color rendition with very low heat
- Great style with no transformer - plugs directly into outlet
- Dimmable with Johnson Controls dimmer (triac type)
- Available with a panel bracket, clamp, or table base



(Double Arm with base shown)

BALLAST/TRANSFORMER (120V/60HZ)	none required
SWITCHING	on/off
LAMP (BULB)	
WATTS	35
TYPE	halogen
RATED LAMP LIFE (HOURS)	2,000
LUMEN OUTPUT	625
COLOR RENDERING INDEX	100
COLOR TEMPERATURE	3000K
REPLACEMENT LAMP, ANSI, 35 WATT	FMW/GU10/FR (silverized reflector only)
REPLACEMENT LAMP, 35 WATT	22503 (JOLT)
	35FMW/GU10/FR (LIGHTBULBDIRECT.COM)



Turbo can also be used with a 20 watt lamp for environments where the 35 watt lamp would be continuously dimmed to 50% levels for more than half the time. In this case it would be best to use a 20 watt lamp.

REPLACEMENT LAMP, ANSI, 20 WATT	BAB/GU10 (clear cover glass)
REPLACEMENT LAMP, 20 WATT	B620120 (BULBS.COM)

HEAD	
DIMENSIONS (L X W X H)	4" x 4" x 3"
REFLECTOR	symmetrical
FINISH COLOR	black or gray
THERMAL PROTECTION	equipped with a temperature sensor that will prevent the use of dichroic reflector lamps, and/or lamps greater than 35 watts

ARM	
DOUBLE ARM LENGTH	30"
MATERIAL	aluminum
ARM FINISH	black or silver paint
JOINT MATERIAL	technopolymer
JOINT COLOR	black or gray
JOINT ADJUSTABILITY	thumb screws
CORD LENGTH, DOUBLE ARM	6'
CORD COLOR	black or gray

APPROVALS / STANDARDS CSA (NRTL)

PHOTOMETRICS (35 WATT LIGHT LEVELS)

15" ABOVE WORKSURFACE	80 fc
20" ABOVE WORKSURFACE	43 fc
25" ABOVE WORKSURFACE	29 fc

